ALTERRA 450





ALTERRA° 450





MID-SIZED FOR MORE EXPLORING

The Alterra 450 is built with durable features such as superior 7-in. travel suspension, expansive 1,050-lb towing capacity and horsepower that doesn't back down. Proving itself with the reliability of a liquid-cooled engine and impact-resistant bodywork, this machine is engineered to excel in every category from performance to comfort to price.

KEY FEATURES

- 443 cc Single-Cylinder EFI Engine
- 7-in. Suspension Travel
- 10.2-in. Ground Clearance
- Rear 2-in. Receiver Hitch
- On-the-Fly 2WD/4WD
- Digital Gauge with Dual Front Halogen Headlights
- Double A-Arm Front and 2WD/4WD with Selectable Front Differential Lock Rear Suspension
- 75-lb Front Rack and 150-lb Rear Rack Capacity

	ALTERRA 450
ENGINE & DRIVETRAIN	
ENGINE TYPE	Liquid-Cooled, Single Cylinder
DISPLACEMENT	443cc
DRIVETRAIN	CVT
DRIVE SYSTEM	2WD/4WD Manual Actuation
FUEL SYSTEM	EFI (Electronic Fuel Injection)
GEAR SELECTION	H,L,N,R,P
FRONT DIFFERENTIAL	2WD / 4WD Open
REAR DIFFERENTIAL	Locked
STEERING & SUSPENSIO	N
STEERING	Standard
FRONT SUSPENSION	Double A-Arm with 7.5-in. (19 cm) Travel
REAR SUSPENSION	Double A-Arm with 7-in. (18 cm) Travel
BRAKE SYSTEM	Dual Front Hydraulic Disc, Single Rear Hydraulic Disc
FOOT BRAKE	Foot Operated Rear Brake
PARKING BRAKE	Hydraulic Parking Brake
FRONT TIRES	25x8-12
REAR TIRES	25x10-12
WHEELS	Steel
PERFORMANCE	
TOTAL CAPACITY	440 lb (199.5 kg)
FRONT RACK	75 lb (34 kg)
REAR RACK	150 lb (68 kg)
TOWING CAPACITY	1,050 lb (476 kg)
DIMENSIONS	
OVERALL LENGTH	83.9-in. [213 cm]
OVERALL WIDTH	44-in. (111.8 cm)
OVERALL HEIGHT	46.9-in. (119 cm)
OVERALL WEIGHT (DRY)	613 lb (278 kg)
WHEELBASE	47.7-in. (121 cm)
GROUND CLEARANCE	10.2-in. (25.9 cm)
FUEL CAPACITY	4.3 gal (19.5 L)
HITCH	Standard 2-in. Receiver
COLOR OPTIONS	
STANDARD COLORS	Coyote Tan, Smokescreen Grey
FEATURES	6
SKID PLATE	Standard Full Length
INSTRUMENTATION	Multifunction Digital Gauge
LIGHTING	Dual Halogen Headlight and Dual Halogen Brakelight/Taillight
START METHOD	Electric Start
WARRANTY	12 Months





