

# ALTERIA 700











## ALTERRA 700

ALTERRA 700 FPS

### ALTEDDA 700 VI

# RIDE FIRST CLASS.

Built with a premium suspension system and electronic power steering (EPS and XT models), this machine rides easy, and goes hard on the trail. With class-leading 10-inch front and rear suspension travel, 11-inch ground clearance, and a 1,050-lb towing capacity, you can ride anywhere or get anything done. Smooth rides, a sleek design, and unmatched power come standard with Alterra 700.

# **KEY FEATURES**

- Single-Cylinder Closed-Loop EFI Engine
- Class-Leading 10-inch Front and Rear Suspension Travel
- Electronic Power Steering (EPS & XT)
- 11-in Ground Clearance
- 1,050-lb Towing Capacity
- Durable Steel Racks
- Premium Machined-Aluminum Wheels (XT)
- Carlisle® Trail Pro® Tires
- Rear 2-inch Hitch Receiver
- · Adjustable Front Shock Absorbers
- Digital Gauge

# **NEW ALTERRA 700 ENGINE FEATURES**

The new Textron Motors 700 engine provides a reduction in weight and increased overall performance and handling.

- Reduced engine rotational mass weight
- Direct drive clutch
- Newly designed CVT cover
- · New camshaft grind

	ALTERRA 700	ALTERRA 700 EPS	ALTERRA 700 XT	
ENGINE & DRIVETRAIN				
NGINE TYPE	Liquid-Cooled,	Single Cylinder Single Overhead C	am, Gas Engine	
DISPLACEMENT(CC)	695cc			
RIVETRAIN	***************************************	CVT		
RIVE SYSTEM	RTS (Rapid Tra	RTS (Rapid Traction System)		
UEL SYSTEM	RTS (Rapid Traction System)			
NGINE BRAKING SYSTEM	Standard			
EAR SELECTION	H,L,N,R,P			
RONT DIFFERENTIAL	2/4WD Di	2/4WD Differential		
REAR DIFFERENTIAL		Rear Gear Case		
TEERING & SUSPENS	ION			
TEERING	N/A Electronic Power Steering			
RONT SUSPENSION	Double A-Arm with 10-inch (25 cm) Travel			
EAR SUSPENSION	Double A-Arm with 10-inch (25 cm) Travel			
RAKE SYSTEM	Single Lever Front, All Wheel Hydraulic Disc			
OOT BRAKE	Hydraulic Rear			
ARKING BRAKE	Park in Transmission			
RONT TIRES	25 x 8 - 12			
EAR TIRES	25 x 10 - 12			
/HEELS	Powder-Coated Steel		Machined Aluminum	
ERFORMANCE				
OTAL CAPACITY	515 lb (233.6 kg)			
RONT RACK	100 lb (45.3 kg)			
EAR RACK	200 lb (90.7 kg)			
OWING CAPACITY	1,050 lb (476 kg)			
IMENSIONS		, , ,		
VERALL LENGTH	83.4 in (212 cm)			
VERALL WIDTH	48.5 in (123 cm)			
VERALL HEIGHT	49.5 in (125.7 cm)			
VERALL WEIGHT	699 lb (317 kg) (Dry)			
VHEELBASE	52 in (132 cm)			
ROUND CLEARANCE	11 in (28 cm)			
UEL CAPACITY	5.7 gal (21.6 L)			
IITCH	Standard/2-inch (5 cm) Receiver			
COLOR OPTIONS		Standard/2-men (3 em) Necerver		
KID PLATE		Standard		
	Dunamia Casu	Earth Blue	Fire Red	
TANDARD COLORS	Dynamic Gray			
PTIONAL COLORS	N/A	TrueTimber® Kanati Camo	N/A	
EATURES TANDARD NSTRUMENTATION		neter, Tripmeter, RPM, Gear Indica p, Coolant Temp, Coolant Temp Wa		
ADDITIONAL NSTRUMENTATION	N/A	N/A	2/4WD Diff Lock Indicator	
IGHTING	Dual Beam Headlights, Dual LED Brake Lights/Taillights			
TART METHOD	Duai beaiii neadiignis, Duai EED Brake Eigilis rainignis  Electric Start			
	12 Months			







