

A NEW ERA OF

FOR 60 YEARS, WE'VE SEEN WHAT KIND OF TROUBLE YOU CAN GET INTO ON A FRESH BED OF SNOW. TRAILS THAT BEG YOU TO OPEN THE THROTTLE. MOUNTAINS TO TAME. ADVENTURES TO LAST A LIFETIME. THEY'RE THE JOURNEYS EVERY ARCTIC CAT IS BUILT FOR. WE'VE BEEN RAISING HELL AND RAISING THE BAR SINCE 1962. NOW IT'S YOUR TURN.







The world's fastest production snowmobile gets unprecedented handling, for more control on every thrill ride.



RIOT X WITH ATAC™ A CROSSOVER WITH ADJUSTABLE ON-THE-FLY SUSPENSION

How do you make a true 50/50 crossover snowmobile even more versatile? With shocks that adapt as quickly as the terrain changes, at the push of a button.



BLAST[™] XR + BLAST XR TOURING DOUBLE FUN

BLAST is back with two new ways to double down on fun. The BLAST XR crossover takes adventure anywhere, and the two-seater BLAST XR Touring lets you bring another trouble maker along for the ride.



THE TECH NO OTHER RIDE CAN TOUCH.

Making trouble means making your own way. Nobody else builds a single-beam rear suspension, shocks that change on the fly, or a CVT like this. Because nobody else is Arctic Cat.





ELECTRONIC POWER STEERING

Know what the world's most powerful production snowmobile needs? A new kind of power. We're unleashing Electronic Power Steering on the ZR[®] 9000 Thundercat. Speed freaks and control freaks, unite.




ADJUSTABLE ON-THE-FLY SUSPENSION

The terrain can change quickly. Now you can be ready for whatever comes at you with ATAC[™] Adjustable On-the-Fly Suspension. With the push-button command of three firmness settings, lockout mode and two individual rider profiles, you'll always ride on your terms.

AVAILABLE ON: MOUNTAIN CAT ALPHA ONE, RIOT X, RIOT, ZR 9000 THUNDERCAT EPS, ZR 8000

ATAC's FOX[®] ZERO iQS shocks feature piggyback reservoirs, three compression settings (Soft, Medium and Firm) and two custom rider profiles.











CONTINUOUSLY VARIABLE TRANSMISSION

Bring new life to every ride, with a new transmission that delivers



more consistent performance. longer belt life and less maintenance.


AVAILABLE ON: EVERY FULL-SIZED 2022 ARCTIC CAT



SINGLE-BEAM REAR SUSPENSION

ALPHA ONE[™] unlocks the mountain with the revolutionary single-beam design for incredible maneuverability. With minimal input, you get effortless deep-snow cornering, carving, side-hilling and more. You've never felt a ride like this.

AVAILABLE ON: MOUNTAIN CAT ALPHA ONE, HARDCORE ALPHA ONE, RIOT X, BLAST M



Instead of using a traditional dual-rail suspension, ALPHA ONE has a single aluminum rail that runs right down the center of the track, delivering agility that dual-rail sleds can't match.

The single-beam design of ALPHA ONE eliminates almost all snow accumulation that weighs you down.

05



BLAST XR NEW FOR 2022

- > SLIDE-RAIL REAR SUSPENSION
- > TURN-KEY ELECTRIC START





BLAST M WITH ALPHA ONE™

- > ARCTIC MOUNTAIN FRONT SUSPENSION
- > CHALLENGER TRACK
- > LIGHTWEIGHT ONE-PIECE TUNNEL > TURN-KEY ELECTRIC START

Armed with a powerful, industry-first engine and a best-in-class power-to-weight ratio, the new BLAST Series packs jaw-dropping features into a mid-sized sled. That means faster turns, easier rides and fewer compromises.

MID-SIZED

400 SINGLE-CYLINDER 2-STROKE EFI ENGINE LIGHTWEIGHT MID-SIZED CHASSIS UNRIVALED SUSPENSION TECHNOLOGY **TURN-KEY ELECTRIC START**



MID-SIZED WITH A MEAN STREAK BLAST is the right size for your next adventure: bigger than our ZR 200 youth sleds, but smaller and more

nimble than a full-sized sled.

 \land \land \land

 \land \land \land

 \land \land \land

13

XTRA-ACTION

Take BLAST on the trail or maneuver through the backcountry on our first mid-sized crossover.

> DUAL-SHOCK AND ADJUSTABLE TORSION SPRINGS > ARCTIC MOUNTAIN FRONT SUSPENSION (AMS)



BLAST XR TOURING NEW FOR 2022

Double the fun on BLAST XR Touring, a two-seater built on the mid-sized BLAST frame.

- > 2-UP SEAT
- > SLIDE-RAIL REAR SUSPENSION
- > DUAL-SHOCK, ADJUSTABLE TORSION SPRINGS AND OVERLOAD SPRINGS
- > TURN-KEY ELECTRIC START

Loaded with the agility of ALPHA ONE, the BLAST M is putting higher altitudes on notice.

> ALPHA ONE SINGLE-BEAM REAR SUSPENSION



BLAST ZR[®]

Born with the bloodline of racing champions, the BLAST ZR trail sled is ready to defy a few expectations.

- > SLIDE-RAIL REAR SUSPENSION
- > TRAIL 6 SKI
- > LIGHTWEIGHT ONE-PIECE TUNNEL
- > TURN-KEY ELECTRIC START



BLAST LT

Handle every job on your terms, or just cut loose on the trails. The BLAST LT sport utility sled is designed to let you work hard and play even harder.

- > XTRA-ACTION REAR SUSPENSION
- > STANDARD TUNNEL RACK
- > HIGH WINDSHIELD & RAISED SEAT
- > TURN-KEY ELECTRIC START

arcticcat.com

200

Control of

RDI CROSSOVER

Adjust to any terrain from the trail to the backcountry, with available ATAC[™] Adjustable On-the-Fly Suspension. And for mountain supremacy, RIOT X packs an ALPHA ONE[™] Single-Beam Rear Suspension.

 \land \land \land \land

~ ~ ^ ^ ^

~ ~ ^ ^ ^ ^



RIOT X 8000

- WITH LOCKOUT MODE
- AND REAR TRACK SHOCK
- > AVAILABLE ARCTIC CAT IFP 1.5 SHOCKS





RIOT 8000


- > NEXT GENERATION 800 C-TEC2 165HP-CLASS ENGINE > AVAILABLE ATAC ADJUSTABLE ON-THE-FLY SUSPENSION > ATAC FEATURES 1.5 ZERO IQS SKI SHOCKS AND 2.0 ZERO IOS REAR TRACK SHOCK > ARS™ II FRONT SUSPENSION

Our new Continuously Variable Transmission delivers better performance and longer belt life.

The single-beam design of ALPHA ONE delivers drastically improved maneuverability while eliminating snow pack that can weigh you down.



Adjust your suspension settings instantly to get more from every second of your ride.



- > ARCTIC MOUNTAIN FRONT SUSPENSION > AVAILABLE FOX" 1.5 ZERO QS3 SKI AND TRACK SHOCKS
- > PROCLIMB[™]-7 G2 MOUNTAIN SKIS > 2.6" POWER CLAW™ TRACK
- > PUSH-BUTTON ELECTRIC START

> AVAILABLE FOX 1.5 ZERO QS3 SKI SHOCKS AND FOX 2.0 ZERO OS3 REAR TRACK SHOCK > LIGHTWEIGHT CROSS-ACTION REAR SUSPENSION > PROCLIMB-7 G2 MOUNTAIN SKIS > AVAILABLE ARCTIC CAT IFP 1.5 SHOCKS > PUSH-BUTTON ELECTRIC START



RIOT 6000

- > 600 C-TEC2 125HP-CLASS ENGINE
- > ARS II FRONT SUSPENSION WITH ARCTIC CAT
- IFP 1.5 SKI SHOCKS
- > LIGHTWEIGHT CROSS-ACTION REAR SUSPENSION
- > ARCTIC CAT IFP 2.0 REAR TRACK SHOCK
- > PROCLIMB-7 G2 MOUNTAIN SKIS > PUSH-BUTTON ELECTRIC START

1

Control of

ALPHA MOUNTAIN

On the mountain, control is king. Which is why up here, Arctic Cat reigns, with a revolutionary ALPHA ONE™ Single-Beam Rear Suspension on every mountain sled. For even greater control, step up to ATAC™ Adjustable On-The-Fly Suspension.



4

WITH LOCKOUT MODE AND REAR TRACK SHOCK







- > ASCENDER PLATFORM



M 8000 MOUNTAIN CAT ALPHA ONE

> NEXT GENERATION 800 C-TEC2[™] 165HP-CLASS ENGINE > AVAILABLE ATAC ADJUSTABLE ON-THE-FLY SUSPENSION > ATAC FEATURES FOX® FLOAT 3 IQS SKI SHOCKS

- > AVAILABLE WITH FOX FLOAT QS3 SKI AND TRACK SHOCKS
- > ASCENDER PLATFORM > 3" POWER CLAW™ TRACK > AVAILABLE IN 154" OR 165" TRACK LENGTHS > AVAILABLE PUSH-BUTTON ELECTRIC START

M 8000 HARDCORE ALPHA ONE

- > NEXT GENERATION 800 C-TEC2 165HP-CLASS ENGINE > FOX 1.5 ZERO QS3 SKI AND TRACK SHOCKS > REINFORCED RUNNINGBOARDS AND TWO-PIECE TUNNEL
- > 2.6" OR 3" POWER CLAW TRACK > AVAILABLE IN 146", 154" OR 165" TRACK LENGTHS > AVAILABLE PUSH-BUTTON ELECTRIC START



The only single-beam rear suspension on the mountain lets you side-hill, carve through deep powder and own the backcountry.

ZR TRAIL

We've never been afraid to blaze a trail. So this year, we're giving the world's fastest production snowmobile Electronic Power Steering, making the ZR 9000 Thundercat the unquestioned pack leader. We were born on the trails, and born to make trouble.



ZR 9000 THUNDERCAT®

- > 200+ HP-CLASS 998cc TURBO ENGINE
- > AVAILABLE (EPS) ELECTRONIC POWER STEERING
- > AVAILABLE ATAC ADJUSTABLE ON-THE-FLY SUSPENSION
- > ATAC FEATURES 1.5 ZERO IQS SKI SHOCK AND 2.0 ZERO IOS REAR TRACK SHOCK
- > AVAILABLE FOX 1.5 ZERO QS3 SKI SHOCKS AND FOX 2.0 ZERO QS3 REAR TRACK SHOCK
- > ARS™ II FRONT SUSPENSION > SLIDE-ACTION REAR SUSPENSION
- > PUSH-BUTTON ELECTRIC START

NEW FOR 2022

The world's fastest production snowmobile just got more untouchable. **Electronic Power Steering** makes this the most agile Thundercat yet.





ZR 6000/8000 RR

- > ARS II FRONT SUSPENSION
- > SLIDE-ACTION REAR SUSPENSION





ZR 8000 LIMITED

- > NEXT GENERATION 800 C-TEC2[™] 165HP-CLASS ENGINE
- > ARS II FRONT SUSPENSION
- > SLIDE-ACTION REAR SUSPENSION
- > AVAILABLE ATAC ADJUSTABLE ON-THE-FLY-SUSPENSION WITH LOCKOUT MODE
- > ATAC FEATURES 1.5 ZERO IQS SKI SHOCKS AND 2.0 ZERO IQS REAR TRACK SHOCK
- > AVAILABLE FOX 1.5 ZERO QS3 SKI SHOCKS AND FOX 2.0 ZERO QS3 REAR TRACK SHOCK
- > ELECTRIC START



> NEXT GENERATION 800 C-TEC2 165HP-CLASS ENGINE OR 600 C-TEC2 125HP-CLASS ENGINE > KASHIMA-COATED FOX 1.5 ZERO QS3R SKI SHOCKS > KASHIMA-COATED FOX 1.5 ZERO QS3 FRONT TRACK SHOCK

> KASHIMA-COATED FOX 2.0 ZERO **QS3R REAR TRACK SHOCK** > PUSH-BUTTON ELECTRIC START

ZR 6000 LIMITED

- > 600 C-TEC2 125HP-CLASS ENGINE
- > ARS II FRONT SUSPENSION
- > SLIDE-ACTION REAR SUSPENSION
- > FOX 1.5 ZERO QS3 SKI SHOCKS AND FOX 2.0 ZERO QS3 REAR TRACK SHOCK
- > PUSH-BUTTON ELECTRIC START

1

Control of



There's work to be done. And when the job is over, it's time to cut loose. That's what this work-hard, play-hard vehicle is all about. It's loaded with productivity-focused features that give this trusted Arctic Cat snowmobile an extra load of work ethic.



NORSEMAN X 8000

> NEXT GENERATION 800 C-TEC2™ 165HP-CLASS ENGINE > XTRA-ACTION REAR SUSPENSION > PAINTED CHASSIS > PUSH-BUTTON ELECTRIC START

XTRAACTION ADAPT



ZR° 200

- > 192cc 4-STROKE ENGINE > SSCC TRAIL-CERTIFIED
- > LIGHTWEIGHT REAR SUSPENSION RAILS

- > 5-WAY ADJUSTABLE SHOCKS (FRONT AND REAR)
- > PAINTED CHASSIS
- > TURN-KEY ELECTRIC START

- ZR 120
- > PROVEN 123cc 4-STROKE ENGINE
- > 5-WAY ADJUSTABLE FRONT SHOCKS
- > PAINTED CHASSIS

> HAND WARMERS > COBRA™TRACK

Let's start the next generation of riders early with easy-to-handle snowmobiles

that make them fall in love with riding with every new trail they blaze. These sleds are

built for young riders—whether it's their first time in the seat (ZR 120) or their step

up to trail-certified performance (ZR 200).

arcticcat.com

2022 LINEUP











BLAST LT BLAST XR BLAST XR TOURING BLAST M BLAST KEY TECHNOLOGIES (†Optional) ALPHA ONE COLOR OPTIONS Dynamic Charcoal/Fire Red, Dynamic Charcoal/M STANDARD COLORS Dynamic Charcoal/Gold Dynamic Charcoal/Gold Dynamic Charcaol/Fire Red Dynamic Charcoal/Orange Dynamic Charcoal ENGINE 4000 Series / 2-Stroke / 397cc 4000 Series / 2-Str ENGINE / TYPE / DISPLACEMENT / COOLING / CYLINDERS / Liquid / 1 Cylinder /Liquid/1Cylinder / Liquid / 1 Cylinder / Liquid / 1 Cylinder / Liquid / 1 Cyl FUEL CAPACITY / OIL SYSTEM CAPACITY 11.7 gal / 3.25 gt 11.7 gal / 3.2 DRIVE CLUTCH CVTech Trailbloc CVTech Trailbloc CVTech Trailbloc CVTech Trailbloc CVTech Trail CVTech Invance CVTech Inva CVTech Invance CVTech Invance CVTech Invance DRIVEN CLUTCH USPENSION FRONT SUSPENSION Arctic Mountain Suspension (AMS) Arctic Mountain Suspension (AMS) Arctic Mountain Suspension (AMS) Arctic Mountain Suspension (AMS) Arctic Mountain Susp Slide-Rail, Dual Shock and Slide-Rail, Dual Shock, Adjustable Torsion XTRA-ACTION Rear Suspension with Slide-Rail, Dua REAR SUSPENSION ALPHA ONE Rear Suspension Adjustable Torsion Springs Springs and Overload Springs Dual Shocks and Adjustable Torsion Springs and Adjustable Tors SKI SHOCKS Hydraulic Twin Tube Hydraulic Twin Tube Hydraulic Twin Tube Hydraulic Twin Tube Hydraulic Twir FRONT TRACK SHOCK Hydraulic Twin Tube Hydraulic Twin Tube Hydraulic Twin Tube Hydraulic Twin Tube Hydraulic Twi REAR TRACK SHOCK Hydraulic Twin Tube Hydraulic Twin Tube Hydraulic Twin Tube Hydraulic Twin Tube Hydraulic Twir **CHASSIS & TRACK** CHASSIS OVERALL LENGTH / WIDTH / HEIGHT 128 in. / 44-45 in. / 50.5 in. 128 in. / 46-47 in. / 50.5 in. 128 in. / 44-46 in. / 38.5 in. 128 in. / 44-45 in. / 50.5 in. 115 in. / 44-45 in TRACK TYPE Cobra Ripsaw Challenger Cobra Standar TRACK WIDTH / LENGTH / LUG 15 in. / 146 in. / 1.60 in. 15 in. / 146 in. / 1.25 in. 15 in. / 146 in. / 2 in. 15 in. / 146 in. / 1.60 in. 14 in. / 121 in. SKI STANCE 37.5-38.5 in. Adjustable 39.5-40.5 in. Adjustable 37-39 in. Adjustable 37.5-38.5 in. Adjustable 37.7-38.5 in. Ad STARTER Turn-key Electric Start Turn-key Electric Start Turn-key Electric Start Turn-key Electric Start Turn-key Electr HEADLIGHTS Halogen 1-Bulb Halogen 1-Bulb Halogen 1-Bulb Halogen 1-Bulb Halogen 1-I WINDSHIELD 4 in. Low-Height 15.5 in. High-Height 4 in. Low-Height 15.5 in. High-Height 4 in. Low-He Hand and Thumb Warmers, Tether Switch, Hand and Thumb Warmers, Tether Switch, Hand and Thumb Warmers, Tether Switch, Hand and Thumb Warmer, Rear Rack, Hand and Thumb Warme STANDARD FEATURES Digital Gauge , Digital Gauge Digital Gauge Tether Switch, Digital Gauge Digital Gau







ZR	M 8000 MOUNTAIN CAT ALPHA ONE	M 8000 HARDCORE ALPHA ONE				
	ALPHA ONE, ATAC ⁺ , ADAPT	ALPHA ONE, ADAPT				
Medium Green, al/Skye Blue	Dynamic Charcoal/Skye Blue	Orange/Black, Medium Green/Black				
troke / 397cc Cylinder	8000 C-TEC2 / 2-Stroke / 794cc / Liquid / 2 Cylinder	8000 C-TEC2 / 2-Stroke / 794cc / Liquid / 2 Cylinder				
3.25 qt	10.4 or 11.7 gal* / 3.25 qt	10.4 or 11.7 gal* / 3.25 qt				
ailbloc	ADAPT CVT	ADAPT CVT				
vance	ADAPT CVT	ADAPT CVT				
spension (AMS)	Arctic Mountain Suspension (AMS)	Arctic Mountain Suspension (AMS)				
ial Shock rsion Springs	ALPHA ONE Rear Suspension	ALPHA ONE Rear Suspension				
vin Tube	FOX FLOAT 3 QS3 or FOX FLOAT 3 iQS	FOX 1.5 ZERO QS3 COIL-OVER				
vin Tube	FOX FLOAT 3 QS3 or Arctic Cat IFP 1.5	FOX 1.5 ZERO QS3 COIL-OVER				
<i>v</i> in Tube	FOX FLOAT 3 QSL or FOX FLOAT 3 iQSL	FOX 1.5 ZERO QSL COIL-OVER				
in. / 38 in.	132 or 137 in. / 42.5-44.5 in. / 50 in.	131/132/137 in. / 42.5-44.5 in. / 50 in.				
rd	Power Claw	Power Claw				
n. / 1 in.	15 in. / 154 or 165 in. / 3 in.	15 in. / 146 or 154 or 165 in. / 2.6 or 3 in.				
djustable	35.5-37.5 in. Adjustable	35.5-37.5 in. Adjustable				
tric Start	Manual or Push-Button Electric Start	Manual or Push-Button Electric Start				
-Bulb	LED with Accent Light	LED with Accent Light				
Height	1 in. Mountain-Height	1 in. Mountain-Height				
ner, Tether Switch, auge	12V Outlet, Goggle Holder, Hand and Thumb Warmers, Ice Scratchers, Lightweight Mountain Brake Disc, Sport Front Bumper, Tether Switch, Vertical Steering, Deluxe Digital Gauge	12V Outlet, Goggle Holder, Hand and Thumb Warmers, Ice Scratchers, Lightweight Mountain Brake Disc, Sport Front Bumper, Tether Switch, Vertical Steering, Deluxe Digital Gauge				

*11.7 gallon fuel tank offered with electric start option and 10.4 gallon tank offered without electric start option. *11.7 gallon fuel tank offered with electric start option and 10.4 gallon tank offered without electric start option.



BUILD YOUR SLED

Use our new online builder to craft your perfect ride, compare options and buy.

 \sim

 \sim

 $\mathbf{\mathbf{\nabla}}$

 \checkmark

 \sim

SNOWMOBILE BUILDER

arcticcat.com/build

 \sim

 $\mathbf{\nabla}$

 \sim

 \sim

 \sim

 \sim

arcticcat.com 17













	NEW								
	RIOT X 8000	RIOT 8000	RIOT 6000	ZR 9000 THUNDERCAT	ZR 6000/8000 RR	ZR 6000/8000	NORSEMAN X 8000	ZR 200 ES	ZR 120
EY TECHNOLOGIES (*Optional)	ALPHA ONE, ATAC ⁺ , ADAPT	ATAC⁺, ADAPT	ADAPT	EPS ⁺ , ATAC ⁺ , ADAPT	ADAPT	ATAC⁺, ADAPT	ADAPT		
OLOR OPTIONS									
STANDARD COLORS	Dynamic Charcoal/Fire Red, Orange	Dynamic Charcoal/Medium Green, Dynamic Charcoal/Fire Red	Dynamic Charcoal/Medium Green	Dynamic Charcoal	Medium Green	Dynamic Charcoal/Orange, Dynamic Charcoal/Medium Green	Dynamic Charcoal/Fire Red	Fire Red, Dynamic Charcoal/Electrolime, Dynamic Charcoal/Medium Green	Medium Green
NGINE									
NGINE / TYPE / DISPLACEMENT / COOLING / CYLINDERS	8000 C-TEC2 / 2-Stroke / 794cc / Liquid / 2 Cylinder	8000 C-TEC2 / 2-Stroke / 794cc / Liquid / 2 Cylinder	6000 C-TEC2 / 2-Stroke / 599cc / Liquid / 2 Cylinder	9000 C-TEC4 / 4-Stroke / 998cc / Liquid / 3 Cylinder - Turbocharged	6000 C-TEC2 / 2-Stroke / 599cc / Liquid / 2 Cylinder 8000 C-TEC2 / 2-Stroke / 794cc / Liquid / 2 Cylinder	6000 C-TEC2 / 2-Stroke / 599cc / Liquid / 2 Cylinder 8000 C-TEC2 / 2-Stroke / 794cc / Liquid / 2 Cylinder	8000 Series / 2-Stroke / 794cc / Liquid / 2 Cylinder	200 / 4-Stroke / 192cc / Air / 1 Cylinder	120 / 4-Stroke / 123cc / Air / 1 Cylinder
UEL CAPACITY / OIL SYSTEM CAPACITY	11.7 gal / 3.25 qt	11.7 gal / 3.25 qt	11.7 gal / 3.25 qt	9.9 gal / 3.8 qt	11.7 gal / 3.25 qt	11.7 gal / 3.25 qt	13.7 gal / 3.25 qt	2.2 gal / 0.6 qt	0.5 gal / 0.6 qt
DRIVE CLUTCH	ADAPT CVT	ADAPT CVT	ADAPT CVT	ADAPT CVT	ADAPT CVT	ADAPT CVT	ADAPT CVT	Arctic 5.25 in. Diameter (RPM Sensing)	Arctic Centrifugal
RIVEN CLUTCH	ADAPT CVT	ADAPT CVT	ADAPT CVT	ADAPT CVT	ADAPT CVT	ADAPT CVT	ADAPT CVT	Arctic 6.75 in. Diameter (Roller Cam)	N/A
SUSPENSION									
RONT SUSPENSION	Arctic Mountain Suspension (AMS)	Arctic Race Suspension (ARS) II	Arctic Race Suspension (ARS) II	Arctic Race Suspension (ARS) II	Arctic Race Suspension (ARS) II	Arctic Race Suspension (ARS) II	Arctic Race Suspension (ARS)	Arctic Wishbone Suspension (AWS)	Arctic Wishbone Suspension (AWS)
EAR SUSPENSION	ALPHA ONE Rear Suspension	CROSS-ACTION with 3 Wheel Rear Axle Assembly, Torque-Sensing Link Rear Arm and Adjustable Torsion Springs.	CROSS-ACTION with 3 Wheel Rear Axle Assembly, Torque-Sensing Link Rear Arm and Adjustable Torsion Springs.	SLIDE-ACTION with 3 Wheel Rear Axle Assembly, Coupling Blocks, Torque-Sensing Link Rear Arm and Adjustable Torsion Springs.	SLIDE-ACTION with 3 Wheel Rear Axle Assembly, Coupling Blocks, Torque-Sensing Link Rear Arm and Adjustable Torsion Springs	SLIDE-ACTION with 3 Wheel Rear Axle Assembly, Coupling Blocks, Torque-Sensing Link Rear Arm and Adjustable Torsion Spring	XTRA-ACTION Rear Suspension with adjustable torsion springs and Torque-Sensing Link rear arm	Slide-Rail, Adjustable Torsion Spring, Coil-Over Rear Shock	Slide-Rail, Adjustable Torsion Spring
KI SHOCKS	Arctic Cat IFP 1.5 or FOX 1.5 ZERO QS3 Coil-Over or FOX 1.5 ZERO iQS Coil-Over	Arctic Cat IFP 1.5 or FOX 1.5 ZERO QS3 or FOX 1.5 ZERO iQS	Arctic Cat IFP 1.5	FOX 1.5 ZERO QS3 or FOX 1.5 ZERO iQS	FOX 1.5 ZERO QS3R KASHIMA	FOX 1.5 ZERO QS3 or FOX 1.5 ZERO iQS	Arctic Cat IFP 1.5	Hydraulic Twin Tube	Hydraulic Twin Tube
RONT TRACK SHOCK	Arctic Cat IFP 1.5 or FOX 1.5 ZERO QS3 Coil-Over	Arctic Cat IFP 1.5	Arctic Cat IFP 1.5	Arctic Cat IFP 1.5	FOX 1.5 ZERO QS3 KASHIMA	Arctic Cat IFP 1.5	Arctic Cat IFP 1.5	N/A	N/A
REAR TRACK SHOCK	Arctic Cat IFP 1.5 or FOX 1.5 ZERO QSL Coil-Over or FOX 1.5 ZERO iQSL Coil-Over	Arctic Cat IFP 2.0 or FOX 2.0 ZERO QS3 or FOX 2.0 ZERO iQS	Arctic Cat IFP 2.0	FOX 2.0 ZERO QS3 or FOX 2.0 ZERO iQS	FOX 2.0 ZERO QS3R KASHIMA	FOX 2.0 ZERO QS3 or FOX 2.0 ZERO iQS	Arctic Cat IFP 1.5	Hydraulic Twin Tube	N/A
HASSIS & TRACK									
HASSIS OVERALL LENGTH / WIDTH / HEIGHT	131 in. / 46.5-48.5 in. / 49 in.	132 in. / 48-49 in. / 48 in.	132 in. / 48-49 in. / 48 in.	125 in. / 48-49 in. / 52 in.	125 in. / 48-49 in. / 48 in.	125 in. / 48-49 in. / 48 in.	132 in. / 45.5-51.5 in. / 52 in.	84 in. / 35-37 in. / 36 in.	73 in. / 35-37 in. / 34 in.
RACK TYPE	Power Claw	Cobra	Cobra	Ripsaw II	Ripsaw II	Ripsaw II	Power Claw	Cobra	Cobra
RACK WIDTH / LENGTH / LUG	15 in. / 146 in. / 2.60 in.	15 in. / 146 in. / 1.35 or 1.60	15 in. / 146 in. / 1.60 or 1.35 in.	15 in. / 137 in. / 1.25 in.	15 in. / 137 in. / 1.25 in.	15 in. / 137 in. / 1.25 in.	15 in. / 153 in. / 2.25 in.	10 in. / 93 in. / 1 in.	10 in. / 67 in. / 0.75 in.
KI STANCE	39.5-41.5 in. Adjustable	41.5-43.5 in. Adjustable	41.5-43.5 in. Adjustable	42-43 in. Adjustable	42-43 in. Adjustable	42-43 in. Adjustable	35.5-41.5 in. Adjustable	29.5-31.5 in. Adjustable	29.5-31.5 in. Adjustable
EATURES									
TARTER	Push-Button Electric Start	Push-Button Electric Start	Push-Button Electric Start	Push-Button Electric Start	Push-Button Electric Start	Push-Button Electric Start	Push-Button Electric Start	Turn-key Electric Start	Manual
EADLIGHTS	Dual Halogen 2-Bulb or LED with Accent Light	Dual Halogen 2-Bulb or LED with Accent Light	Dual Halogen 2-Bulb	LED with Accent Light	LED with Accent Light	LED with Accent Light	Dual Halogen 2-Bulb	Halogen 1-Bulb	Halogen 1-Bulb
VINDSHIELD	1 in. Mountain-Height	5.5 in. Race-Height	5.5 in. Race-Height	11 in. Mid-Height	5.5 in. Race-Height	11 in. Mid-Height	14 in. Mid-Height	4 in. Low-Height	4 in. Low-Height
STANDARD FEATURES	12V Outlet, Brake Disc, Goggle Holder, Hand and Thumb Warmers, Ice Scratchers, Sport Front Bumper, Vertical Steering, Tether Switch, Deluxe Digital Gauge	12V Outlet, Hand and Thumb Warmers, Ice Scratchers, Sport Front Bumper, Standard Brake Disc, Steering, Tether Switch, Deluxe Digital Gauge	12V Outlet, Brake Disc, Hand and Thumb Warmers, Ice Scratchers, Sport Front Bumper, Standard Steering, Tether Switch, Deluxe Digital Gauge	12V Outlet, Goggle Holder, Handguards, Hand and Thumb Warmers, Heated Drivers Seat, Sport Front Bumper, Standard Brake Disc, Standard Steering, Tether Switch, Tunnel Flare, Deluxe Digital Gauge	12V Outlet, Handguards, Hand and Thumb Warmers, Sport Front Bumper, Lightweight Performance Brake Disc, Standard Steering, Tether Switch, Deluxe Digital Gauge	12V Outlet, Goggle Holder, Hand and Thumb Warmers, Sport Front Bumper, Standard Brake Disc, Standard Steering, Tether Switch, Tunnel Flare, Deluxe Digital Gauge	Hand and Thumb Warmers, Front Sport Bumper, Tow Hitch, Rear Rack, Tether Switch, 12V Outlet, Deluxe Digital Gauge	Brake Disc, Hand and Thumb Warmers, Steering, Tether Switch, Youth Front Bumper	Brake Disc, Hand Warmers, Safety Flag, Steering, Tether Switch, Youth Front Bumper









arcticcat.com

SPECS

- \wedge
- •

- ~ /
- ~ ~
- \wedge



Every Arctic Cat is designed in Minnesota and assembled

by American workers in the town of Thief River Falls.

That means your sled is built with pride,

right in the heart of snowmobiling country.

arcticcat.com

Snowmobiling is serious fun. Be sure to read and understand your owner's manual and please pay special attention to the safety instructions. Arctic Cat Inc. endorses and encourages the safe use of all snowmobiles. Be careful; you can get hurt. Wear an approved helmet and don't drink and ride. Be aware of natural hazards you may encounter, allow yourself plenty of room to safely stop your snowmobile under all conditions, and maintain your equipment. Your safety is in your hands, so take care. All scenes depicted or described in this brochure were performed by professional riders under carefully controlled conditions. Leave the fancy riding to the pros; they practice for years and train very hard to make it look easy. Never attempt to duplicate these maneuvers or encourage others to do so. We care about your safety and enjoyment of the sport. All materials and specifications are subject to change without notice. All specifications, competitive specifications, claims and information contained within are based on current knowledge and readily available printed material available as of January 1, 2021. All rights reserved. Cobra^M and RipsawTM are trademarks of Canso Inc. Diamond Direct DriveTM is a trademark of Black Diamond, Inc. FOX[®], FOX FLOAT[®] and FOX[®] ZERO are registered trademarks of FOX Racing Shox. TEAM[®] Rapid ResponseTM is a trademark of Arctic Cat[®], Arctic Wishbone SuspensionTM, Arctic Cat[®], Arctic Mountain SuspensionTM, Arctic Race SuspensionTM, ARSTM, AscenderTM, Arctic Wishbone SuspensionTM, MWSTM, Bearcat[®], C-TEC2TM, C-TEC2TM, ATACTM, Mountain Cat[®], Power ClawTM, ProClimbTM, SLIDE-ACTION Rear SuspensionTM, Son CrossTM, Team Arctic[®], Thoutercat[®], Son ChasTM, TeactTM, Teact^T